



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 009-002
Product name Disinfectant Spray For Hospital Use
Effective date 01-Sep-2011
Company information Claire Mfg.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 01

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE
CONTENTS UNDER PRESSURE.
Will be easily ignited by heat, spark or flames. Contact with eyes may cause irritation.
Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Skin contact. Ingestion.

Eyes Moderately irritating to the eyes.

Skin Harmful if absorbed through the skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.
Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Unconsciousness. Cyanosis (blue tissue condition, nails, lips, and/or skin). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Jaundice. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Ethyl Alcohol	64-17-5	40 - 50
n-Butane	106-97-8	15 - 20
Propane	74-98-6	5 - 8
Methanol	67-56-1	1 - 3
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center immediately.

Skin contact Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Get medical attention if symptoms persist.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water jet.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Wear personal protective equipment. Avoid prolonged exposure.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Methanol	67-56-1	200 ppm	250 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Methanol	67-56-1	200 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Chemical goggles are recommended.
Skin protection	Chemical resistant gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	136.4 °F (57.8 °C) estimated
Color	clear colorless
Density	0.7518 g/cm ³ estimated
Flammability (HOC)	24.953 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Alcoholic.
pH	9.5 - 10.5
Physical state	Liquid.
Pressure	70 - 80 psig @70F
Solubility	Partially
Specific gravity	0.7519

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h
Methanol	67-56-1	Inhalation LC50 Rat 83.2 mg/L 4 h; Inhalation LC50 Rat 64000 ppm 4 h; Oral LD50 Rat 5628 mg/kg; Dermal LD50 Rabbit 15800 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol	64-17-5	Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in preparation] (in alcoholic beverages)
---------------	---------	--

Teratogenicity Animal experiments showed mutagenic and teratogenic effects.

12. Ecological Information

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

LC50 1762 mg/L, Fish, 96.00 Hours,
EC50 952 mg/L, Daphnia, 48.00 Hours,
IC50 569 mg/L, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Methanol 67-56-1 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Methanol: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol	64-17-5	Present
Methanol	67-56-1	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 3
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Prepared by

Regulatory Compliance