



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 700-005
Product name Xtreme Gleme All Weather Surface Degreaser
Effective date 04-Mar-2011
Company information Claire Mfg.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 08
Supersedes date 26-Jul-2010

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Harmful in contact with eyes.

Potential health effects

Routes of exposure Eye contact. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion. May cause delayed lung damage. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Central nervous system. Lungs.

Chronic effects Unconsciousness. Conjunctiva. Cyanosis (blue tissue condition, nails, lips, and/or skin). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Jaundice. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

| Components | CAS # | Percent |
|--|----------|---------|
| Ethyl Alcohol | 64-17-5 | 5 - 8 |
| Diethylene Glycol Monobutyl Ether | 112-34-5 | 3 - 5 |
| n-Butane | 106-97-8 | 1 - 3 |
| Non-hazardous and other components below reportable levels | | 80 - 90 |

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Get medical attention if symptoms persist.

Ingestion If material is ingested, immediately contact a poison control center.

Notes to physician Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

| | |
|--|---|
| Flammable properties | Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard. |
| Extinguishing media | |
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Protection of firefighters | |
| Protective equipment and precautions for firefighters | In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. |

6. Accidental Release Measures

| | |
|--------------------------------|---|
| Methods for containment | Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. |
| Methods for cleaning up | Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |

7. Handling and Storage

| | |
|-----------------|--|
| Handling | Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. |
| Storage | Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep container dry. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 1 Aerosol (NFPA 30B) |

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

| Components | CAS # | TWA | STEL | Ceiling |
|-----------------------------------|----------|----------|-----------------|-----------------|
| Ethyl Alcohol | 64-17-5 | 1000 ppm | 1000 ppm | Not established |
| Diethylene Glycol Monobutyl Ether | 112-34-5 | 20 ppm | Not established | Not established |
| n-Butane | 106-97-8 | 1000 ppm | Not established | Not established |

OSHA

| Components | CAS # | TWA | STEL | Ceiling |
|-----------------------------------|----------|----------|-----------------|-----------------|
| Ethyl Alcohol | 64-17-5 | 1000 ppm | Not established | Not established |
| Diethylene Glycol Monobutyl Ether | 112-34-5 | 100 ppm | Not established | Not established |

Personal protective equipment

| | |
|-------------------------------|--|
| Eye / face protection | Do not get in eyes. Chemical goggles are recommended. |
| Skin protection | Wear appropriate chemical resistant clothing. Chemical resistant gloves. |
| Respiratory protection | When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. |

9. Physical & Chemical Properties

| | |
|----------------------|------------------------------------|
| Appearance | Compressed liquefied gas. |
| Boiling point | 213.8 °F (101.1 °C) estimated |
| Color | Cloudy. |
| Density | 0.9597 g/cm ³ estimated |

| | |
|---------------------------|--------------------------------|
| Flammability (HOC) | 4.6332 kJ/g estimated |
| Flash back | No |
| Flash point | -156 °F (-104.4 °C) Propellant |
| Form | Aerosol. |
| Freezing point | Not available |
| Odor | Characteristic. |
| pH | 9.5 - 10.5 |
| Physical state | Liquid. |
| Pressure | 65 - 70 psig @70F |
| Solubility | Partially |
| Specific gravity | 0.9598 estimated |

10. Chemical Stability & Reactivity Information

| | |
|---|--------------------------|
| Chemical stability | Risk of ignition. |
| Conditions to avoid | Heat, flames and sparks. |
| Hazardous decomposition products | Irritants. Toxic gas. |

11. Toxicological Information

Acute effects Acute LD50: 54188 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

| | | |
|-----------------------------------|----------|--|
| Diethylene Glycol Monobutyl Ether | 112-34-5 | Oral LD50 Rat 3384 mg/kg; Dermal LD50 Rabbit 2700 mg/kg |
| Ethyl Alcohol | 64-17-5 | Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h |
| n-Butane | 106-97-8 | Inhalation LC50 Rat 658 mg/L 4 h |

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

| | | |
|---------------|---------|--|
| Ethyl Alcohol | 64-17-5 | Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in preparation] (in alcoholic beverages) |
|---------------|---------|--|

12. Ecological Information

Ecotoxicity LC50 20896 mg/L, Fish, 96.00 Hours,
 EC50 23978 mg/L, Daphnia, 48.00 Hours,
 IC50 5503 mg/L, Algae, 72.00 Hours,
 Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

| | |
|------------------------------|--|
| Waste codes | D001: Waste Flammable material with a flash point <140 F |
| Disposal instructions | Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. |

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

| | |
|--------------------------------|--------------------|
| Proper shipping name | Consumer commodity |
| Hazard class | ORM-D |
| Subsidiary hazard class | None |
| Additional information: | |
| Packaging exceptions | 156, 306 |
| Packaging non bulk | 156, 306 |
| Packaging bulk | None |

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Item 5F
Labels required None
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



| |
|-----------------------------------|
| 15. Regulatory Information |
|-----------------------------------|

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Diethylene Glycol Monobutyl Ether 112-34-5 1.0 % de minimis concentration (applies to R-(OCH₂CH₂)_n-OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of New and Existing Chemicals (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

| | | |
|-----------------------------------|----------|----------------------|
| Diethylene Glycol Monobutyl Ether | 112-34-5 | Environmental hazard |
| Ethyl Alcohol | 64-17-5 | Present |
| n-Butane | 106-97-8 | Present |

16. Other Information

| | |
|------------------------------|---|
| Further information | HMIS® is a registered trade and service mark of the NPCA. |
| HMIS® ratings | Health: 1 Flammability: 2 Physical hazard: 0 |
| Disclaimer | The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. |
| MSDS sections updated | This document has undergone significant changes and should be reviewed in its entirety. |
| Prepared by | Regulatory Compliance |