



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 120
Product name Lemon Lime Metered Air Freshener
Effective date 12-Nov-2007
Company information Claire Manufacturing
500 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Supersedes date 06-Jul-2007

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame.

OSHA regulatory status Harmful in contact with eyes. Prolonged exposure may cause chronic effects.
This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects
Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Central nervous system. Respiratory system.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

Signs and symptoms Corneal damage. Narcosis. Conjunctivitis.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	70 - 80
Propane	74-98-6	10 - 15
n-Butane	106-97-8	10 - 15
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures
Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
Skin contact Immediately take off all contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops or persists.
Inhalation Call a physician if symptoms develop or persist.
Ingestion Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention.

Notes to physician Symptoms may be delayed.

General advice If you feel unwell, seek medical advice (show the label where possible).

5. Fire Fighting Measures

Flammable properties Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

Extinguishing media

Suitable extinguishing media Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Protective equipment and precautions for firefighters In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.

Methods for containment Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Avoid contact with eyes. Avoid prolonged exposure.

Storage Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Not normally needed.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas.

Color Clear.

Odor fruity

Physical state Liquid.

Form	Aerosol.
Flammability (HOC)	31.8312 kJ/g estimated
Flash back	No
Pressure	65 - 75 psig @ 70F
Solubility	Partially
Flash point	-156 °F (-104.4 °C) estimated
Boiling point	66.2 °F (18.9 °C) estimated
Specific gravity	0.734 estimated
pH	Not applicable

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects	Acute LD50: 2571 mg/kg estimated, Rat, Oral Acute LD50: 28567 mg/kg estimated, Rat, Dermal Acute LC50: 108 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Contact may irritate or burn eyes.
Chronic effects	Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
Neurological effects	Hazardous by OSHA criteria.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.
Epidemiology	Not expected to be hazardous by OSHA criteria.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicity	LC50 7906 mg/L estimated, Fish, 96.00 Hours, EC50 17952 mg/L estimated, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental concerns.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F D018: Waste Benzene
Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None

Additional information:

Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS, flammable
Hazard class 2.1
UN number 1950
Additional information:
Item 5F
Labels required 2.1
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Chemical	Inventory ID	Inventory Status
Acetone	67-64-1	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

HMIS® ratings

Health: 1
 Flammability: 4
 Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

12-Nov-2007