



# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000010104  
**Product identifier** **PENETRATING COIL CLEANER**  
**Company information** Claire Manufacturing Co.  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
**Company phone** General Assistance 1-630-543-7600  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Recommended use** Cleaner  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Acute toxicity, inhalation Category 4  
Serious eye damage/eye irritation Category 2  
Sensitization, skin Category 1  
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation  
**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3  
Hazardous to the aquatic environment, long-term hazard Category 3  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol. May cause an allergic skin reaction. Causes serious eye irritation.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye/face protection. Wear protective gloves.  
**Response** If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse.  
**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
2-Butoxyethanol		111-76-2	1 - 2.5
Diethylene Glycol Monoethyl Ether		111-90-0	1 - 2.5
EDTA Tertrasodium Salt		64-02-8	1 - 2.5
Propane		74-98-6	1 - 2.5
d-Limonene		5989-27-5	0.1 - 1
Sodium Nitrite		7632-00-0	0.1 - 1
Other components below reportable levels			80 - 90

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
<b>Skin contact</b>	Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention. For minor skin contact, avoid spreading material on unaffected skin.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	In the unlikely event of swallowing contact a physician or poison control center.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes and mucous membranes. May cause allergic skin reaction.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Pay attention to flashback. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. This material and its container must be disposed of as hazardous waste. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get this material in contact with skin. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not empty into drains.

**Conditions for safe storage, including any incompatibilities**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
Propane (CAS 74-98-6)	PEL	50 ppm
		1800 mg/m3 1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
Butane (CAS 106-97-8)	TWA	5 ppm
		1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	TWA	140 mg/m3
		25 ppm

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

### US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

## Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Hand protection** Wear protective gloves.

### Skin protection

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

<b>Appearance</b>	Compressed liquefied gas.
<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Color</b>	Colorless.
<b>Odor</b>	Characteristic.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	212 °F (100 °C) estimated
<b>Flash point</b>	-156.0 °F (-104.4 °C) Propellant estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.

<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	65 - 75 psig @ 70F estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.969 g/cm3 estimated estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.94 g/cm3 estimated
<b>Flammability class</b>	Flammable IB estimated
<b>Heat of combustion (NFPA 30B)</b>	2.93 kJ/g estimated
<b>Percent volatile</b>	97.03 % estimated
<b>Specific gravity</b>	0.969 estimated estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Exposure to air. Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Oxygen. Do not mix with other chemicals. None known.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**Eye contact** Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** Acute LD50: 11169 mg/kg, Rat, Dermal  
May cause allergic skin reaction.

Product	Species	Test Results
PENETRATING COIL CLEANER (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	11169 mg/kg
<i>Inhalation</i>		
LC50	Rat	112 mg/l/4h

Product	Species	Test Results
<i>Oral</i> LD50	Rat	
<b>Components</b>	<b>Species</b>	<b>Test Results</b>
2-Butoxyethanol (CAS 111-76-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	230 ml/kg, 24 Hours 7.3 ml/kg, 4 Days
	Rabbit	450 ml/kg, 24 Hours 435 mg/kg, 24 Hours 0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
<i>Oral</i>		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1200 mg/kg
	Rat	530 - 2800 mg/kg
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	5900 mg/kg, Days
	Rabbit	8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg
<i>Oral</i>		
LD50	Guinea pig	4970 mg/kg
	Mouse	6031 mg/kg
	Rabbit	5600 mg/kg
	Rat	5600 mg/kg 5.4 ml/kg
EDTA Tetrasodium Salt (CAS 64-02-8)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Rat	1658 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes

Components	Species	Test Results
	Rat	1355 mg/l 658 mg/l/4h
Sodium Nitrite (CAS 7632-00-0)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	5.5 mg/kg, 4 hours supplier
<i>Oral</i>		
LD50	Rat	88 mg/kg supplier

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Not expected to be hazardous by OSHA criteria.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.
<b>Carcinogenicity</b>	Not expected to be hazardous by WHMIS criteria. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
d-Limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
	Not listed.
<b>Reproductive toxicity</b>	Not expected to be hazardous by OSHA criteria.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
	Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood.
<b>Further information</b>	Symptoms may be delayed.

## 12. Ecological information

<b>Ecotoxicity</b>	LC50: 557 mg/L, Fish, 96.00 Hours EC50: 959 mg/L, Daphnia, 48.00 Hours IC50: 65.75 mg/L, Algae, 72.00 Hours Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.
--------------------	--

Product	Species	Test Results
PENETRATING COIL CLEANER (CAS Mixture)		
<b>Aquatic</b>		
Algae	IC50	Algae 65.7535 mg/L, 72 Hours
Crustacea	EC50	Daphnia 959 mg/L, 48 Hours
Fish	LC50	Fish 557 mg/L, 96 Hours
<b>Components</b>	<b>Species</b>	<b>Test Results</b>
2-Butoxyethanol (CAS 111-76-2)		
<b>Aquatic</b>		
Fish	LC50	Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

Components	Species	Test Results
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus) > 10000 mg/l, 96 hours
d-Limonene (CAS 5989-27-5)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia pulex) 69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours
EDTA Tertrasodium Salt (CAS 64-02-8)		
<b>Aquatic</b>		
Algae	IC50	Algae 1.01 mg/L, 72 Hours
Fish	LC50	Bluegill (Lepomis macrochirus) 472 - 500 mg/l, 96 hours
Sodium Nitrite (CAS 7632-00-0)		
<b>Aquatic</b>		
Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis) 16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.15 - 0.25 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

2-Butoxyethanol	0.83
Butane	2.89
Diethylene Glycol Monoethyl Ether	-0.54
d-Limonene	4.232
Propane	2.36

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	None
<b>Packing group</b>	Not applicable.



**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** N82

**Packaging exceptions** 306

**Packaging non bulk** None

**Packaging bulk** None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA**

**UN number** UN1950

**UN proper shipping name** Aerosols, flammable

**Transport hazard class(es)**

**Class** 2.1

**Subsidiary risk** -

**Label(s)** 2.1

**Packing group** Not applicable.

**Environmental hazards** No.

**ERG Code** 10L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

**Packaging Exceptions** LTD QTY

**IMDG**

**UN number** UN1950

**UN proper shipping name** AEROSOLS

**Transport hazard class(es)**

**Class** 2.1

**Subsidiary risk** -

**Label(s)** None

**Packing group** Not applicable.

**Environmental hazards**

**Marine pollutant** No.

**EmS** Not available.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**





## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Sodium Nitrite (CAS 7632-00-0) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
 Immediate Hazard - Yes  
 Delayed Hazard - No  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Anhydrous Ammonia	7664-41-7	100	500 lbs		
Benzyl chloride	100-44-7	100	500 lbs		

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Sodium Nitrite	7632-00-0	0.1 - 1

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations**

**US. Massachusetts RTK - Substance List**

2-Butoxyethanol (CAS 111-76-2)  
 Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)  
 Sodium Nitrite (CAS 7632-00-0)

**US. New Jersey Worker and Community Right-to-Know Act**

2-Butoxyethanol (CAS 111-76-2)  
 Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)  
 Sodium Nitrite (CAS 7632-00-0)

## US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Nitrite (CAS 7632-00-0)

## US. Rhode Island RTK

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Nitrite (CAS 7632-00-0)

## US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzyl chloride (CAS 100-44-7)

Listed: January 1, 1990

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 05-30-2015

Version # 01

### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.