

# CL473 TECHNICAL DATA SHEET

## PENETRATING GEL LUBRICANT WITH PTFE



### PRODUCT DESCRIPTION:

- High tack
- Safe on most plastics
- Effective from -30°F to +500°F

A high tack, clear, lubricating gel which provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Deposits a fine polytetrafluoroethylene and gel lubricant mixture deep inside working parts. Resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film. Safe on most plastics.

### USE ON:

Gears, sprockets, hinges, chains, cable, wire rope, slides, valves, pistons, rings, seals, bearings, sleeves, cams and bushings.

### USE BY:

Machine shops, light and heavy manufacturing, HVAC, plumbing and other trades. Automotive and virtually all maintenance or repair operations.

### SPECS:

Can Size: 20 oz.  
Net Weight: 12 oz.  
Shipping Weight: 6.5 Lbs.  
Packaged: 6 cans per case  
Can UPC Number: 7 13014 11473 0  
Carton UPC Number: 10713014014730  
Product Number: CL473  
Extender Tube: No

### REGULATORY:

Ozone Depleting Compounds: None  
Recyclable Package: Yes  
VOC Compliant: Yes  
Flammability: Extremely Flammable

### PHYSICAL CHARACTERISTICS:

Color: White  
Fragrance: Solvent  
Shelf Life: 1 year +

See label side panel for First Aid and additional Precautionary Statements

**24 HOUR MEDICAL EMERGENCY NUMBER:**

**1-866-836-8855**

**KEEP OUT OF REACH OF CHILDREN**

**CONSULT SDS BEFORE USING**



MADE IN THE  
**USA**

Federal regulations prohibit CFC propellants in aerosols.

